


ATTACHMENT A



Serial No. 09/988,508

Patent
0502PUSA

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant: Bernard DOUET
Serial No.: 09/988,508 Group: Unknown
Filed: November 20, 2001 Examiner: Unknown
For: METHOD AND SYSTEM FOR AUTOMATICALLY
DETECTING OR MONITORING THE POSITION OF AT
LEAST ONE GUIDED VEHICLE

ADDITIONAL PRELIMINARY AMENDMENT

Assistant Commissioner of Patents
Washington, DC 20231

March 6, 2002

Sir:

Please amend the Abstract and Claims as set forth hereinbelow and attached hereto as Attachments I, II, and III.

AMENDMENT

IN THE ABSTRACT:

Please delete the Summary ("Abstract") of the English Language Application submitted contemporaneously herewith at Attachment I appended hereto, namely, page 22. It is to be noted that an English Language Abstract was filed as Attachment B by Preliminary Amendment dated November 20, 2001 and is the one to be considered as the Abstract in this Application.

09/988,508, 030602

IN THE CLAIMS:

Please amend the Claims as set forth at Attachment II, with replacement Claims being set forth at Attachment III. It is respectfully noted that the replacement Claims (Attachment III) incorporate the deletions and underlinings set forth in the amended Claims (Attachment II). It is respectfully requested that the claims of Attachment III be substituted for the claims of Attachment II.


REMARKS

The Claims have been amended to clarify the claimed invention and to meet the application format required for prosecution before the United States Patent Office.

The Examiner is invited to contact Andrew F. Reish, Esq., at (703) 903-0334 in the Washington, D.C. area in order to discuss any matters that may remain outstanding.

Respectfully submitted,

DAVID, BRODY & DONDERSHINE, LLP

By: 
Andrew F. Reish
Reg. No. 33,443

8221 Old Courthouse Road, Suite 202
Vienna, VA 22182
(703) 903-0334

Attachments

Attachment I: Abstract to be deleted
Attachment II: Claims as amended
Attachment III: Replacement Claims

209060 80588660

ATTACHMENT I

0998508 030603

ATTACHMENT B

1 6 7

With a procedure and a system for the automatic monitoring and controlling of the position of at least one track-guided vehicle (22), especially of a rail-vehicle, and for emitting of warning signals, whereby in the vehicle, preferable continuously the position of the vehicle (22) is monitored and controlled under use of transmitter/receiver units (18, 19) being implanted in the area of the traveling on tracks respectively (21) and compared with determined respectively previously given data, which refer to the distance to be traveled on, it is foreseen, that the occurrence of dangerous situations from the vehicle (22) warning signals at least to other vehicles (22), being in the local close zone, especially to vehicles (22), which are traveling on a different way than the immediate traveled on way, are emitted, in order to yield an increase of the reliability and the security of fall-outs.]

ATTACHMENT II

Patent claims

1. (Amended) [System] A system for automatically monitoring respectively controlling of the position of at least one track-guided vehicle (22, 37, 40, 42, 43, 44, 45), especially rail-vehicle, and for the emission of warning signals, whereas in the vehicle preferably [continuos] continuous the position of the vehicle (22, 37, 40, 42, 43, 44, 45) under use of transmitter/receiver-units (18, 19, 47) being provided in the area of the traveling over tracks respectively rails (21, 34, 35, 36) and for comparison with the determined respectively previously given data, referring to the route to be traveled on, is characterized that way, that by occurrence of dangerous situations, the vehicle (22, 37, 40, 42, 43, 44, 45) sends warning signals at least to other vehicles (22, 37, 40, 42, 43, 44, 45) being in the local close zone, especially to those, which are traveling on a different way from the immediate passing over way.
2. (Amended) [System] The system according to [patent] claim 1, is characterized that way, that from a vehicle (22, 37, 40, 42, 43, 44, 45) different warning signals corresponding to different dangerous situations are emitted.
3. (Amended) [System] The system according to [patent] claim 1[or 2], characterized that way, that from the vehicle (22, 37, 40, 42, 43, 44, 45) furthermore preferably continuous data concerning the position and identification of these vehicles (22, 37, 40, 42, 43, 44, 45) being in the local close zone, and/or to control stations are transmitted.
4. (Amended) (System) The system according to [patent] claim 1[, 2 or 3], characterized that way, that the vehicle (22, 37, 40, 42, 43, 44, 45) receives preferably continuous from other vehicles (22, 37, 40, 42, 43, 44, 45) in the local close zone, data concerning the position and identification of these vehicles (22, 37, 40, 42, 43, 44, 45) and compares them with those determined and previously given data concerning the distance to be traveling on and checks if there are possible dangerous situations.

5. (Amended) [System] The system according to [one of the patent claims] claim 1[to 4], characterized that way, that preferably continuous a check-up of the availability of the warning systems and/or a check-up of the functionality of the transmitter-receiver units (18, 19, 47) implanted in the area of the traveling on tracks respectively rails (21, 34, 35, 35) is carried out and that by occurrence of a mistake, warning signals are emitted and/or a stop of the vehicle (22, 37, 40, 42, 43, 44, 45) is effected.
6. (Amended) [A] The system according to [one of the patent claims] claim 1[to 5], characterized I that way, that the transmitter-receiver units (18, 19, 47), which are implanted in the area of the traveling on tracks respectively rails (21, 34, 35, 36) are equipped with an encoding e.g., geographic co-ordinates.
7. (Amended) [A] The system according to [one of the patent claims] claim 1[to 6], characterized in that way, that a storage at least of the data of the previous transmitter-receiver units is carried out, and these data together with identification-data of the vehicle (22, 37, 40, 42, 43, 44, 45) are emitted with the emission of warning signals.
8. (Amended) [A] The system according to [one of the patent claims] claim 1[to 7], characterized in that way that warning signals are transferred via preferably internationals alarm-or warning frequencies.
9. (Amended) A system for the automatic monitoring and controlling of position of at least one track-guided vehicle, especially rail-vehicle and for the emission of warning signals, whereas the vehicle (22, 37, 40, 42, 43, 44, 45) consists of at least one unit (2) for the monitoring and controlling of the position under use of transmitter-receiver units (18, 19, 47) which are integrated in the area of the traveling on tracks respectively rails (21, 34, 35, 36) and for comparison with the determined respectively previously given data referring to the way to be traveled on, characterized in this way, that furthermore a unit (2) is foreseen for emission and receiving of warning signals at least to other vehicles (22, 37, 40, 42,[42] 43, 44, 45) being in the local close zone, especially to those traveling on another way than the way immediate passing over by occurrence of dangerous situations.

202508-030602

10. (Amended) [A] The system according to [patent] claim 9, characterized in that way, that the units (18, 19) implanted in the area of the rails respectively tracks (21, 34, 35, 36) at least consist of one unit for emission of a signal that marks the position of the unit respectively an encoding, e.g., of geographic co-ordinates.
11. (Amended) [A] The system according to [patent] claim 9[or 10], characterized in that way, that additionally a unit for receiving an storage of key data of the vehicle of the vehicle (22, 37, 40, 42, 43, 44, 45) is foreseen.
12. (Amended) [A] The system according to [patent] claim 9, [10 or 11,]characterized in that way, that units are foreseen for the monitoring and controlling the position as well in the front area (22), especially in the locomotive or a driving element, as also in the back side (22'), especially at the last wagon.
13. (Amended) [A] The system according to [one of the patent claims] claim 9[to 12], characterized in that way, that in the vehicle (22, 37, 40, 42, 43, 44, 45) the units (2, 3, 4, 8) for the monitoring and controlling the position, for comparison with data referring to the distance and for emitting and for receiving for warning signals are coupled with a common control-and arithmetic unit (1) or preferable are integrated in this one.
14. (Amended) [A] The system according to [one of the patent claims] claim 9[to 13], characterized in that way, that the unit (2) for emission and for receiving a warning signals is coupleable with driving units of the vehicle (22, 37, 40, 42, 43, 44, 45) and by occurrence of dangerous situations an influence of driving parameters of the vehicle, e.g., a reducing the speed by braking, is feasible.
15. (Amended) [A] The system according to [one of the patent claims] claim 9[to 14] characterized in that way, that the units (18, 19, 47) implanted in the area of the tracks respectively rails (21, 34, 35, 36) consist of transponder and/or units for a laser marking.

16. (Amended) [A] The system according to [one of the patent claims] claim 9[to 15], characterized in that way, that the transfer of signals, especially warning signals, is carried out via wireless or cable connection, especially a glass fibre cable, respectively via the rail (21).
17. (Amended) [A] The system according to [one of the patent claims] claim 9[to 16], characterized in that way, that at respectively in the vehicle (22, 37, 40, 42, 43, 44, 45) additional displays, are foreseen, especially light signals units, for the displaying of the functionality of the system.

0550500.030600
"0900" 9050500

0990508 030603

ATTACHMENT III

Patent claims

1. A system for automatically monitoring respectively controlling of the position of at least one track-guided vehicle (22, 37, 40, 42, 43, 44, 45), especially rail-vehicle, and for the emission of warning signals, whereas in the vehicle preferably continuous the position of the vehicle (22, 37, 40, 42, 43, 44, 45) under use of transmitter/receiver-units (18, 19, 47) being provided in the area of the traveling over tracks respectively rails (21, 34, 35, 36) and for comparison with the determined respectively previously given data, referring to the route to be traveled on, is characterized that way, that by occurrence of dangerous situations, the vehicle (22, 37, 40, 42, 43, 44, 45) sends warning signals at least to other vehicles (22, 37, 40, 42, 43, 44, 45) being in the local close zone, especially to those, which are traveling on a different way from the immediate passing over way.
2. The system according to claim 1, is characterized that way, that from a vehicle (22, 37, 40, 42, 43, 44, 45) different warning signals corresponding to different dangerous situations are emitted.
3. The system according to claim 1, characterized that way, that from the vehicle (22, 37, 40, 42, 43, 44, 45) furthermore preferably continuous data concerning the position and identification of these vehicles (22, 37, 40, 42, 43, 44, 45) being in the local close zone, and/or to control stations are transmitted.
4. The system according to claim 1, characterized that way, that the vehicle (22, 37, 40, 42, 43, 44, 45) receives preferably continuous from other vehicles (22, 37, 40, 42, 43, 44, 45) in the local close zone, data concerning the position and identification of these vehicles (22, 37, 40, 42, 43, 44, 45) and compares them with those determined and previously given data concerning the distance to be traveling on and checks if there are possible dangerous situations.
5. The system according to claim 1, characterized that way, that preferably continuous a check-up of the availability of the warning systems and/or a check-up of the functionality of the transmitter-receiver units (18, 19, 47) implanted in the area of

the traveling on tracks respectively rails (21, 34, 35, 36) is carried out and that by occurrence of a mistake, warning signals are emitted and/or a stop of the vehicle (22, 37, 40, 42, 43, 44, 45) is effected.

6. The system according to claim 1, characterized in that way, that the transmitter-receiver units (18, 19, 47), which are implanted in the area of the traveling on tracks respectively rails (21, 34, 35, 36) are equipped with an encoding e.g., geographic co-ordinates.
7. The system according to claim 1, characterized in that way, that a storage at least of the data of the previous transmitter-receiver units is carried out, and these data together with identification-data of the vehicle (22, 37, 40, 42, 43, 44, 45) are emitted with the emission of warning signals.
8. The system according to claim 1, characterized in that way that warning signals are transferred via preferably international alarm-or warning frequencies.
9. A system for the automatic monitoring and controlling of position of at least one track-guided vehicle, especially rail-vehicle and for the emission of warning signals, whereas the vehicle (22, 37, 40, 42, 43, 44, 45) consists of at least one unit (2) for the monitoring and controlling of the position under use of transmitter-receiver units (18, 19, 47) which are integrated in the area of the traveling on tracks respectively rails (21, 34, 35, 36) and for comparison with the determined respectively previously given data referring to the way to be traveled on, characterized in this way, that furthermore a unit (2) is foreseen for emission and receiving of warning signals at least to other vehicles (22, 37, 40, 42, 43, 44, 45) being in the local close zone, especially to those traveling on another way than the way immediately passing over by occurrence of dangerous situations.
10. The system according to claim 9, characterized in that way, that the units (18, 19) implanted in the area of the rails respectively tracks (21, 34, 35, 36) at least consist of one unit for emission of a signal that marks the position of the unit respectively an encoding, e.g., of geographic co-ordinates.

20090208 095858

11. The system according to claim 9, characterized in that way, that additionally a unit for receiving an storage of key data of the vehicle of the vehicle (22, 37, 40, 42, 43, 44, 45) is foreseen.
12. The system according to claim 9, characterized in that way, that units are foreseen for the monitoring and controlling the position as well in the front area (22), especially in the locomotive or a driving element, as also in the back side (22'), especially at the last wagon.
13. The system according to claim 9, characterized in that way, that in the vehicle (22, 37, 40, 42, 43, 44, 45) the units (2, 3, 4, 8) for the monitoring and controlling the position, for comparison with data referring to the distance and for emitting and for receiving for warning signals are coupled with a common control-and arithmetic unit (1) or preferable are integrated in this one.
14. The system according to claim 9, characterized in that way, that the unit (2) for emission and for receiving a warning signals is coupleable with driving units of the vehicle (22, 37, 40, 42, 43, 44, 45) and by occurrence of dangerous situations an influence of driving parameters of the vehicle, e.g., a reducing the speed by braking, is feasible.
15. The system according to claim 9 characterized in that way, that the units (18, 19, 47) implanted in the area of the tracks respectively rails (21, 34, 35, 36) consist of transponder and/or units for a laser marking.
16. The system according to claim 9, characterized in that way, that the transfer of signals, especially warning signals, is carried out via wireless or cable connection, especially a glass fibre cable, respectively via the rail (21).
17. The system according to claim 9, characterized in that way, that at respectively in the vehicle (22, 37, 40, 42, 43, 44, 45) additional displays, are foreseen, especially light signals units, for the displaying of the functionalibility of the system.